FANTON
FABBRICA MATERIALE ELETTRICO

Scheda tecnica/Data Sheet: 73020



DESCRIZIONE PRODOTTO / PRODUCT DESCRIPTION

Lng.	Descrizione / Description
IT	Convertispina OPTIMUS da cantiere IP44 spina 2P+T 16A 200-250V 6h IP44 presa bipasso italo/Schuko 2P+T 16A
EN	OPTIMUS converter plug for industrial purposes IP44 plug 2P+E 16A 200-250V 6h IP44 socket italian 10-16A/Schuko std. 2P+E 16A

CARATTERISTICHE PRINCIPALI / FEATURES

Lng.	Caratteristica / Feature	Valore / Value
IT	Tipo spina	2P+T 16A 230V 6h IP44
IT	Numero prese/uscite	1
IT	Tipo prese	Bipasso Ital/Sck 2P+T 16A
IT	Colore	Grigio-Blu
IT	Confezione singola	Talloncino appendibile
IT	Protezione IP	IP44
IT	Marchi qualità	CE
IT	Classificazione ELECTROCOD	22.0.0
EN	Plug type	2P+E 16A 230V 6h IP44
EN	Number sockets/outlets	1
EN	Sockets type	It 10-16A/Schuko 2P+E 16A

Lng.	Caratteristica / Feature	Valore / Value
EN	Colour	Grey-Blue
EN	Single packaging	Hanging package
EN	Ingress protection	IP44
EN	Quality marks	CE
EN	ELECTROCOD classification	22.0.0

CARATTERISTICHE ETIM / ETIM FEATURES

Lng.	Caratteristica / Feature	Um	Valore / Value
IT	Tipologia		Singolo
IT	Con spina per AUS (AS/NZS 3112) (tipo I)		No
IT	Con spina per BE/DE/NL/RU (contatto di protezione, tipo F)		No
IT	Con spina per BE / DE / NL / RU / CH (Euro) (tipo C)		No
IT	Con spina per CH (SEV 1011 tipo 11) (tipo J)		No
IT	Con spina per CH (SEV 1011 tipo 12) (tipo J)		No
IT	Con spina per CH (SEV 1011 tipo 23) (tipo J)		No
IT	Con spina per FR (pin di terra) (tipo E)		No
IT	Con spina per UK/HK (BS 1363) (tipo G)		No
IT	Con spina per IT (S/P 11)		No
IT	Con spina per IT (S/P 17) (tipo L)		No
IT	Con spina per USA/CA/CN (NEMA 1-15) (tipo A)		No
IT	Con spina per USA/CA/CN (NEMA 5-15) (tipo B)		No
IT	Tipo di presa		Altro
IT	Numero di porte USB		0
IT	Colore		Grigio
IT	Tensione nominale	V	Da 200 a 250
IT	Corrente nominale	A	Da 0 a 0
EN	Model		Single
EN	With plug for AU/NZ/PG/AR (AS/NZS 3112) (type I)		No
EN	With plug for BE/DE/NL/RU (protective contact CEE 7/4, type F)		No
EN	With plug for BE/DE/NL/RU/CH (Euro) (type C)		No
EN	With plug for CH (SEV 1011 type 11) (type J)		No
EN	With plug for CH (SEV 1011 type 12) (type J)		No
EN	With plug for CH (SEV 1011 type 23) (type J)		No
EN	With plug for FR (earth pin) (type E)		No
EN	With plug for UK/HK (BS 1363) (type G)		No
EN	With plug for IT (S/P 11)		No
EN	With plug for IT (S/P 17) (type L)		No
EN	With plug for US/CA/CN (NEMA 1-15) (type A)		No
EN	With plug for US/CA/CN (NEMA 5-15) (type B)		No
EN	Type of bus		Other
EN	Number of USB ports		0
EN	Colour		Grey
EN	Nominal voltage	V	From 200 to 250
EN	Nominal current	A	From 0 to 0

Fanton s.r.l. si riserva di apportare modifiche e migliorie al prodotto in qualsiasi momento e senza alcun preavviso

Fanton s.r.l. reserves the right to change and update the product at any time and without warning.

Date: 03/04/2026